



INSTANT SHOWER HEATER N3230SH



MADE IN MALAYSIA



SPLASH PROOF IP25 STANDARD



EARTH LEAKAGE CIRCUIT BREAKER



ANTI-SCALD PROTECTION

Rated Voltage	: 230V 50/60Hz
Rated Power	: 3.3kW
Min. Water Flow	: 2 L/m
Min. Inlet Water Pressure	: 0.2 Bar (0.02Mpa)
Max. Inlet Water Pressure	: 3 Bar (0.3Mpa)
Heater Tank	: Polymer
Product Dimensions	: H360 x W240 x D96 MM
Packaging Dimensions	: L570 x W268 x H112 MM
Net Weight	: 1.4 KG
Gross Weight	: 2.6 KG



INSTANT SHOWER HEATER N8280SH



MADE IN MALAYSIA



SPLASH PROOF IP25 STANDARD



EARTH LEAKAGE CIRCUIT BREAKER



ANTI-SCALD PROTECTION

Rated Voltage	: 230V 50/60Hz
Rated Power	: 3.3kW
Min. Water Flow Rate	: 2 L/m
Min. Inlet Water Pressure	: 0.2 Bar (0.02Mpa)
Max. Inlet Water Pressure	: 3 Bar (0.3Mpa)
Heater Tank	: Polymer
Product Dimensions	: H425 x W200 x D95 MM
Packaging Dimensions	: L570 x W268 x H112 MM
Net Weight	: 1.5 KG
Gross Weight	: 2.7 KG



INSTANT SHOWER HEATER N8380SH



MADE IN MALAYSIA



SPLASH PROOF IP25 STANDARD



EARTH LEAKAGE CIRCUIT BREAKER



ANTI-SCALD PROTECTION

Rated Voltage	: 230V 50/60Hz
Rated Power	: 3.3kW
Min. Water Flow Rate	: 2 L/m
Min. Inlet Water Pressure	: 0.2 Bar (0.02Mpa)
Max. Inlet Water Pressure	: 3 Bar (0.3Mpa)
Heater Tank	: Copper
Product Dimensions	: H425 x W200 x D95 MM
Packaging Dimensions	: L570 x W268 x H112 MM
Net Weight	: 1.7 KG
Gross Weight	: 2.9 KG